



**TRANSPORT, RECOVERY & LASHING PRODUCTS  
CATALOGUE - 2019/2020**



HANDLING EQUIPMENT  
CANTERBURY



Fittings - Rated G70 .....	4
G70 Chain & Sets .....	7
Tiedowns .....	10
Corner Boards .....	17
Loadbinders - Chain Twitch .....	18
Recovery Equipment .....	21



# TRANSPORT, RECOVERY & LASHING PRODUCTS

# Fittings - Rated G70

## Grab Hook - Clevis Wing



### Features

- Grade 70 with Cradle Support.

Size	Lashing Capacity (t)	Code
6mm	2.3	2862
7.3 - 8 mm	3.8	2337
10mm	6	2338
13mm	9	2339

## Grab Hook - Clevis



### Features

- Grade 70 with NO Wing's or Cradle.
- Lashing Capacities Comply with AS/NZS4344.
- These style hook will derate your lashing capacity by 20%.

Size	Lashing Capacity (t)	Code
7.3 - 8mm	3.8	9265
10mm	6	9266

## Grab Hook - Weld On



### Features

- Grade 70.
- Complies with NZS 4344.3.8.
- Suit 7.3mm & 8.0mm G70 Chain.

Size	Lashing Capacity (t)	Code
7.3 - 8mm	3.8	9271

## AG-Type Clevis Grab Hook



### Features

- Replacement Hooks for Agri Trailer Safety Chain Sets.

Size	Lashing Capacity (t)	Code
10mm	5	3964
13mm	10	4079

## Fittings - Rated G70

### Claw Hook - Clevis



#### Features

- Claw type fitting that holds the chain with two claws.

Size	Lashing Capacity (t)	Code
6-8mm	3.8	5921
10mm	6	5920

### Lug Link - Clevis



#### Features

- G70 Gold Clevis Lug Link.

Size	Lashing Capacity (t)	Code
8mm	3.8	2340
10mm	6	2341
13mm	9	2342

### Slip Hook - Clevis



#### Features

- G70 Gold Clevis Slip Hook.

Size	Lashing Capacity (t)	Code
6mm	2.3	3113
8mm	3.8	3114
10mm	6	3115
13mm	9	3116

### Sling Hook - Eye Forged c/w Latch



#### Features

- Safety Factor 5:1.
- Supplied with Latch.
- Rating Marked on Hook.

Working Load Limit (t)	Code
0.75	5616
1	5617
1.5	5618
2	5619
3	5620

## Fittings - Rated G70

### Web Strap Loadchoker



#### Features

- Strap Load Chokers are engineered and designed for application with 50mm (2") and 100mm(4") webbing straps.
- Manufactured to international standards, both sizes are ideal for restricting load movement when transporting belly wrapped loads. Manufactured and tested to: AS/NZS 4380 and EN 12195-2.

Size	Lashing Capacity (t)	Code
50mm	2.5	8722

### Chain Load Choker



#### Features

- Chain Load Chokers are engineered and designed for application with 8mm (5/16") and 10mm (3/8") G70 transport chains.
- Manufactured to international standards, both sizes are ideal for restricting load movement when transporting belly wrapped loads.
- Manufactured and tested to AS/NZS 4344 and EN 12195-3.

Size	Lashing Capacity (t)	Code
8mm	3.8	8648
10mm	6	8721





## Fittings - Rated G70

### Twin Clevis Link - SLR G70



#### Features

- Ideal for joining G70 Transport Chain.
- Forged Alloy Steel.
- Quenched & Tempered.

Size	Lashing Capacity (t)	Code
6-8mm	4.2	5622
10mm	6	5623
13mm	10.2	5624

### 4X4 Tow Hook



#### Features

- Black Power Coated Protection.
- Supplied with Latch, Bolts & Nuts.
- Forged Alloy Steel.
- Quenched & Tempered.

Working Load Limit (t)	Code
4.5	5595

## G70 Chain & Sets

### HDG Trailer Chain



#### Features

- Grade 70 Long Link Chain.
- Hot Dipped Galvanised Coating.
- Rated Minimum 2:1 Safety Factor.
- Complies with LTSA & Standards NZS5467.
- Stamped with Standard & Batch Identification.

Size	Working Load Limit (t)	Code
10mm	3.5	9280

Drum Size	Pail
100 m	27 m

## G70 Chain & Sets

### Transport Chain Set



#### Features

- AMG G70 Gold Bucket.
- Lashing Chain with Cradle Grab Hook at Both Ends.
- Supplied with Batch I.D. Tag and Certificate.
- Complies with NZ LTSA Truck Loading Code.
- To PWB AS/NZS4344 Marking Specification 2:1.

Size	Lashing Capacity (t)	Chain Length	Code
7.3mm	3	6m	2348
7.3mm	3	9m	2349
8mm	3.8	9m	2350
10mm	6	9m	2351

### Snig Chain



#### Features

- Chain fitted with Grab Hook & Lug Link.
- Metal ID Tag with Rating fitted.
- Supplied in Plastic Pails.

Size	Drawbar Pull (t)	Chain Length	Code
8mm	2.5	5m	2673
10mm	4	4m	2674
10mm	4	5m	2675
10mm	4	6m	2676

### Agri G70 Safety Trailer Chain Set



#### Features

- Agricultural Safety Chain is designed to fit between the towing connection on an agricultural trailer and a tractor.
- Fitted with offset link on one end and grab hook with safety latch on the other end.

Size	Rating (t)	Chain Length	Code
10mm	5	1.5m	3072
13mm	10	1.5m	3073



## G70 Chain & Sets

### Transport G70 Chain



Drum Size

100 m

#### Features

- Complies with NZ LTSA Truck Loading Code.
- To PWB AS/NZS4344 Marking Specifications 2:1.
- Sold Per Metre and Drum.

Size	Lashing Capacity (t)	Code
6mm	4.6	2663
7.3mm	6	2960
8mm	7.6	3407
10mm	12	5661
13mm	18	2847

### Trailer Chain



Drum Size 8mm

Drum Size Pail

100 m

42m

Drum Size 10mm

Drum Size Pail

100 m

27m

#### Features

- Grade 70 Long Link.
- Gold Passivated Coating.
- Rated Minimum 2:1 Safety Factor.
- To LTSA & Standards NZS5467.

#### Marking on Chain

- 5467 (NZ Standard No.).
- G70 (Grade of High Tensile Chain).
- AMG 3 (Traceability Batch No.).

Size	Working Load Limit (t)	Code
8mm	2.5	5664
10mm	3.5	5292

### 8mm Trailer Chain Set



#### Features

- Chain and Shackle has all relevant markings and safety factors required under the New Zealand LTSA. Standards NZS5467.
- 1 x 2.5T HDG Multi-Fit Trailer Shackle 11.7mm Pin.
- 1 x Safety Chain Insert Washer (To Suits M12 Bolt).

Size	Rating (t)	Code
10 Link	2.5	7870
12 Link	2.5	8852

# Tiedowns

These TiTAN Tie Downs EXCEED the minimum 2:1 Safety Factor required on all components used to manufacture this item under New Zealand Standards.  
The webbing used is Ultra Violet Light (U.V.) resistant for added protection.



## 5T Titan Rat HK/KPR

### Features



- Heavy Haulage.
- 5000kg Lashing Capacity (LTSA Guidelines).
- 80mm Wide Industrial Webbing.
- Industrial Quality Ratchet.
- Inner Eye Hook & Keeper Protection.
- Red 8.5m Mainstrap (Includes HK/KPR).
- Yellow 9.5m Mainstrap (Includes Wear Sleeves HK/KPR).
- 0.5m Tailstrap (Includes Ratchet & HK/KPR).
- Labelled and Certified to NZS4380.
- Batch Identification Number.
- 4 Per Box.

Code Red	Yellow
6120	2779

## Tiedowns



### 3T Titan HD Blue Rat HK/KPR 9.0M

#### Features

- 3000kg Lashing Capacity (LTSA Guidelines).
- 50mm Heavy Royal Blue Webbing (7.5T MBL).
- Industrial Heavy Ratchet.
- Hook & Keeper at Ends (HK/KPR).
- 2 Sliding Protection Sleeves.
- 8.5m Mainstrap (Includes HK/KPR).
- 0.5m Tailstrap (Includes Ratchet & HK/KPR).
- Labelled and Certified to NZS4380.
- Batch Identification Number.
- 10 Per Box.

Code

5183



### 2.5T Titan Green 12.5m c/w Sleeves

#### Features

- Water Tank Straps.
- 2500kg Lashing Capacity (LTSA Guidelines).
- 50mm Industrial Webbing (6.5T MBL).
- Industrial Quality Ratchet.
- Hook & Keeper at Ends (HK/KPR).
- 2 Sliding Protection Sleeves.
- 12.0m Mainstrap (Includes HK/KPR).
- 0.5m Tailstrap (Includes Ratchet & HK/KPR).
- Labelled and Certified to NZS4380.
- Batch Identification Number.
- 10 Per Box.

Code

7869



### 2.5T Embroidered Name in Webbing 9.0M

#### Features

- Quality NZ made strap and ratchet with your choice of wording woven into the webbing. 2500kg.
- Length - 9m (other lengths also available).

Code

3417

# Tiedowns



## 2.5T Titan 9.0M

### Features

- 2500kg Lashing Capacity (LTSA Guidelines).
- 50mm Wide Industrial Webbing.
- Industrial Quality Ratchet / Truckies.
- Inner Eye Hook & Keeper Protection (HK/KPR).
- 2 Sliding Protection Sleeves.
- 8.5m Mainstrap (Includes HK/KPR).
- 0.5m Tailstrap (Includes Ratchet & HK/KPR).
- Labelled and Certified to NZS4380.
- Batch Identification Number.
- 10 Per Box .

Code
2352



Step 1  
Fix Straps and Hooks

## 2.5T Side Loading Ratchet 9M

### Features

- Quick and easy ratchet to use – 50mm (2 inch) Heavy duty for the freight industry.
- Lashing Capacity (LC) 2,500kg.
- Breaking Strength 5,000kg.
- Rubber handle with finger grooves.
- Rubber "Release" trigger.
- Galvanized finished.



Step 2  
Open Side Gate



Step 3  
Load Strap into Gate



Step 4  
Begin Ratcheting

Code
7423



## Tiedowns



### 2.5T Titan Main Strap 8.5M

#### Features

- Truckie 50mm.
- "TiTAN" 50mm x 8.5m Blue Webbing Strap.
- Inner Eye Hook & Keeper Protection.

#### Code

3409



### 2.5T Titan Grey J-Hk 9M

#### Features

- Grey Towie - Double J.
- 2500kg Lashing Capacity (LTSA Guidelines).
- 50mm Wide Industrial Webbing.
- Industrial Quality Ratchet.
- Double J Hook at Ends (J/HK).
- 2 Sliding Protection Sleeves.
- 8.5m Mainstrap (Includes J/Hk).
- 0.5m Tailstrap (Includes Ratchet & J/Hk).
- Labelled and Certified to NZS4380.
- Batch Identification Number.
- 10 Per Box.

#### Code

2547



### 2.5T Titan Tail Strap 0.4M

#### Features

- 0.4m Blue Webbing Strap c/w HK/KPR.
- Inner Eye Hook & Keeper Protection.

#### Code

9279



### 1.5T Titan Yellow 6.5M J.Hk

#### Features

- Commercial - Double J.
- 1500kg Lashing Capacity (LTSA Guidelines).
- 37mm Wide Industrial Webbing.
- Industrial Quality Ratchet.
- Double J Hook at Ends (J/HK).
- 6.0m Mainstrap (Includes J/Hk).
- 0.5m Tailstrap (Includes Ratchet & J/Hk).
- Labelled and Certified to NZS4380.
- Minimum Breaking Load 3000kg.
- Batch Identification Number.
- 20 Per Box.

#### Code

2356

## Tiedowns



### 1.5T Titan Industrial Grey 6.5M

#### Features

- 1500kg Lashing Capacity (LTSA Guidelines).
- 37mm Wide Industrial Webbing.
- Industrial Quality Ratchet.
- Hook & Keeper at Ends (HK/KPR).
- 2 Sliding Protection Sleeves.
- 6.0m Main strap (Includes HK/KPR).
- 0.5m Tail strap (Includes Ratchet & HK/KPR).
- Labelled and Certified to NZS4380.
- Batch Identification Number.
- 20 Per Box.

Code

2355



### 1.0T Titan Industrial Yellow 6.5M S/HK

#### Features

- 1T Lashing Capacity (LTSA Guidelines).
- 37mm Industrial Yellow Webbing (4T MBL).
- Industrial Quality Ratchet (3T MBS).
- Labelled and Certified to NZS4380.
- Batch Identification Number.

Code

9281



### 1.0T Titan Industrial Green 6.5M S/HK

#### Features

- 1T Lashing Capacity (LTSA Guidelines).
- 37mm Industrial Green Webbing (4T MBL).
- Industrial Quality Ratchet (3T MBS).
- Heavy 11.0mm Dia "S" Hook (30mm Gap).
- 2 Sliding Protection Sleeves.
- 6.0m Main strap & 0.5m Tail strap.
- Labelled and Certified to NZS4380.
- Batch Identification Number.
- 20 Per Box.

Code

4001

**These TiTAN Tie Downs EXCEED the minimum 2:1 Safety Factor required on all components used to manufacture this item under New Zealand Standards.**

**The webbing used is Ultra Violet Light (U.V.) resistant for added protection.**



## Tiedowns



### 0.75T Titan Industrial Grey Rat HK/KPR 5.5M

#### Features

- 750kg Lashing Capacity (LTSA Guidelines).
- 27mm Wide Industrial Webbing.
- Industrial Quality Ratchet.
- Hook & Keeper at Ends (HK/KPR).
- 2 x Sliding Wear Sleeves.
- 5.0m Main strap (Includes HK/KPR).
- 0.5m Tail strap (Includes Ratchet & HK/KPR).
- Labelled and Certified to NZS4380.
- Batch Identification Number.
- 40 Per Box.

Code

2357



### 0.4T Titan Grey S/HK 5.5M

#### Features

- 400kg Lashing Capacity (LTSA Guidelines).
- 27mm Wide Industrial Webbing.
- Industrial Quality Ratchet.
- "S" Hook at Ends (S/Hk).
- 5.0m Main strap (Includes S/Hk).
- 0.5m Tail strap (Includes Ratchet & S/Hk).
- Labelled and Certified to NZS4380.
- Batch Identification Number.
- 40 Per Box.

Code

2358



### 0.3T Titan Grey Cam S/HK 25mm 3.2M

#### Features

- 27mm Hi Strength U.V. Resistant Grey Webbing.
- Heavy Duty cam buckle.
- 8mm Dia S Hooks at Ends.
- Labelled with Identification Number.
- Complies with LTSA & NZS4380.
- 300kg Lashing Capacity.
- 200mm Tail Strap.
- 3.0m Main Strap.

Code

3117

## Tiedowns



### 2.5T Titan Ratchet 50mm

#### Features

- Suits 2.5T Truckie Tie Downs with standard 50mm webbing straps.
- Marked in accordance with LTSA & NZS4380 Standards.
- Rating: 2500kg Lashing Capacity (5000kg MBL).

**Code**

2996



### Black Theatre

#### Features

- IDEAL for theatre work as almost totally BLACK.
- Industrial Black Polyester Webbing.
- Industrial Black Ratchets.
- Black Powder coated S.Hooks.
- 2 Great Options.

**Size**
**Code**

0.4T L/C Tie Down 25mm x 5.5m (MBL 1.5T)

9282

1.0T L/C Tie Down 35mm x 6.5m (MBL 2.5T)

9283



### Black Wear Sleeve 400mm

#### Features

- Suits 50mm 2.5T Tie Downs.

**Code**

9284



### 1.5T Ratchet Lashing Strap 35mm Yellow Web 6m

#### Features

- 35mm Ratchet Buckle with 35mm x 6m Webbing Tail Only.

**Code**

1241

# Corner Boards



## Steel Corner Protector c/w Rubber Backing

### Features

- 8.0mm Thick Rubber.
- 2.0mm Thick Steel.
- 100mm x 150mm x 100mm.
- 10.0mm Overall Thickness.

#### Code

5251



## Plastic Ribbed Corner Board

### Features

- Strong Ribbed Construction.
- Flexible, Wide & Light Construction.
- 4.0mm Thick Material.
- Dimensions 185mm x 185mm.

#### Length

#### Code

800mm Long

9038

1150mm Long

9039



## Steel Corner Protector

### Features

- 2.0mm Thick Steel.
- 100mm x 150mm x 100mm.
- Zinc Plated.

#### Length

#### Code

100mm Long

5251

## Cargo Corner 1040 Blue H/D

### Features

- Protect your load with Heavy Duty Corner boards.
- Heavy Duty 1040mm Corner Board
- Colour: Blue.

#### Length

#### Code

1040mm

3000



## Plastic Corner Protector

### Features

- Durable and sturdy, ideal for covering load edges.
- Material: Plastic.
- Colour: White.
- Width: 104mm.

#### Length

#### Code

133mm

6988

# Loadbinders - Chain Twitch



## Loadbinder - Lever Type Mini

### Features

- Marked with size, lashing capacity and manufacturers mark.
- Complies with LTSA & AS/NZS4344.

Size	Lashing Capacity (t)	Code
6mm	2.3	2999



## Loadbinder - Lever Type

### Features

- Marked with size, lashing capacity and manufacturers mark.
- Fitted with Winged Grab Hook.
- With exclusively designed Winged Grab Hooks.
- Complies with LTSA & AS/NZS4344.

Size	Lashing Capacity (t)	Code
6-8mm	4	2882
7-10mm	6	3390



## Loadbinder - Re-Coil Less BX600

### Features

- Marked with size, lashing capacity and manufacturers mark.
- Perfect for the Forestry Hauler Trucks.
- The cam release enables easy release of the lever type load binder under load.
- With exclusively designed Winged Grab Hooks.
- Complies with LTSA & AS/NZS4344.

Size	Lashing Capacity (t)	Code
6-8mm	4	9145
7.3-10mm	6	5155

## Loadbinders - Chain Twitch



### Spring Loadbinder - L150

#### Features

- Marked with size, lashing capacity and manufacturers mark.
- High quality forged steel.
- Spring cushion for load protection, cushions shock and sway.
- Binder toggles away from the load.
- Complies with AS/NZS4344.

Size	Lashing Capacity (t)	Code
6-8mm	3.2	9012

## Loadbinder - Ratchet Type



#### Features

- Marked with size, lashing capacity and manufacturers mark.
- With exclusively designed Winged Grab Hooks.
- Complies with AS/NZS4344.



Size	Lashing Capacity (t)	Code
6-8mm	4	2907
7.3-10mm	6	2361
13mm	9	3261

## Loadbinder - Ratchet c/w Fold Away Handle



#### Features

- Marked with size, lashing capacity and manufacturers mark.
- The new safer option with a fold away handle.
- With exclusively designed Winged Grab Hooks.
- Complies with AS/NZS4344.

Size	Lashing Capacity (t)	Code
6-8mm	4	3074

## Loadbinders - Chain Twitch



### Ausbinder Series 3 - 8MM Maxi Binder

#### Features

- Marked with size, lashing capacity and manufacturers mark.
- The LoadMax Patented Maxi Binder.
- Swivel Head Grab Hook.
- Ergonomically Designed.
- Safer, Quicker and Easier to use.
- High Pre-tensioning Force.
- 1/8 Chain Link Length Adjustment.
- Alloy Steel, Heat Treated for Durability.
- Complies with AS/NZS4344.

Size	Lashing Capacity (t)	Code
7.3-8mm	3.8	5515



### Web Dog - Chain Tensioner 3.8T L/C

#### Features

- Ultimate Chain Binder.
- The safe alternative to lever type Loadbinders.
- BlueScope & OneSteel approved.
- Heavy Duty Ratchet.
- 1m of 50mm Heavy Duty Webbing.
- Swivel Cradle Grab Hook Both Ends.
- Wear Sleeve & Inner Eye Protection.

Size	Lashing Capacity (t)	Code
7.3-8mm	3.8	2666

### Extension Bar

#### Features

- Extension Bar 1.0m (Twitch) Extension Bar.



Size	Code
1.0m	2537



# Recovery Equipment



## Teramax Tow Rope

- Compact & Lightweight.
- One of the strongest fibre rope in the world.
- Superior wear life.
- Superior abrasion resistance.
- Customized lengths available.
- Spliced Eyes.
- No stretch.

Minimum breaking Load (t)	Standard Length (m)	Rope Dia (mm)	Code
16	6	12	5634
35	6	18	5324
58	6	24	5635



## Soft Shackle

- Spliced Soft Shackles offer outstanding strength at a fraction of the weight of conventional steel shackles.

Minimum breaking Load (t)	Rope Dia (mm)	Code
30	12	9495
60	18	9496

## Recovery Equipment



### Pulley - 8T Off Road Snatch Block

#### Features

- Titan 4WD Block.
- 8T Pulling Capacity.
- Suits 8mm to 11mm Dia Rope.

**Code**

1074



### 5T Vehicle Tow Strop

#### Features

- 50mm Polyester Webbing.
- Minimum Breaking Load 5000kg.
- Full Eye Protection.
- Length 3.65m.
- Colours: Orange and Green.

**Code  
Green**

7407

**Code  
Orange**

2347



### Titan Big Polyester Towing Line

#### Features

- These Titan Tow Lines allow you to rotate the Endless Sling within the protection cover to reduce eye wear.
- Light weight, flexible and small amount of stretch.
- Cover Sleeve Protection.

Minimum breaking Load (t)	Length (m)	Code
21	9	9293
42	6	9294
42	10	9295
56	10	9296
70	10	9299

## Recovery Equipment



### Industrial Heavy duty tow stropps

#### Features

- Industrial Tow Stropps for heavy towing, up to 48T. Polyester Tow Stropps for those larger. Higher capacities available upon request.
- Nylon Tow Stropps up to 35,000kg, which makes them suitable for snatch recovery. Polyester 45,000kg and greater.

Minimum breaking Load (t)	Length (m)	Code
7.5	6	5835
7.5	9	5837
15	6	5836
15	9	5838
25	6	5839
25	9	5840
35	6	5841
48	6	5842



### Titan Nylon Recovery Strap

#### Features

- 4x4 Recovery Snatch Straps.
- Reinforced Eye Protection.
- 60mm Wide Blue Nylon Webbing.
- 20% Stretch Elongation.

Minimum breaking Load (t)	Length (m)	Code
8	6	8872
8	9	8873

The Titan Recovery strap will allow you to 'snatch' or 'tow' a vehicle which has become bogged, stalled, stuck, or submerged into a recovered position. Manufactured from high tenacity nylon yarn and featuring fully protected formed eyes at each end. It is recommended that the minimum breaking strength of the strap should be between two to three times the Gross Vehicle Mass of any vehicle it is used with.

