

FULL BODY HARNESS

SPECIFICATION FOR 915002QR



Permanent Upright Dorsal D-ring:
 Stamped Alloy Steel with Splitted Polymer Sleeve which prevents the webbing from being damaged by the metallic contact of dorsal D-ring. MBS 23kN, Proof Load Tested.



Quick Release Buckle: Extremely easy to use with single hand. Designed with lock indicator. Made of stamped alloy steel, MBS: 15kN.



Adjustable Buckle: provided with pull grip feature to enable easy pull down with thumb and easy to adjust straps for a good lift.



Snap Hook: Made of forged Alloy Steel, Double Action, MBS 23kN, 20mm Opening with thumb and easy to adjust straps for a good lift.



Product Label: with protection sleeve.



Fall arrest & Retrieval attachment loops: The loops at the ends are protected by an abrasion resistant covering. This prevents the webbing from being damaged by the metallic contact of the connector.



Elastic Loops: Designed to retain the excess strap while adjustment.



Abrasion Resistant Covering: prevents the webbing from being damaged by metallic contact of the connector.



Energy Absorber: The special webbing inside the energy absorber takes up most of the shock when a fall occurs.

REF.

915002QR

SIZES

Standard = M-XL



MAX. 140 KG

(Instruction Manual - HLPN-2021-V1.2)

AS/NZS

Harness - AS/NZS 1891.1:2020 / Lanyard - AS 1891.5:2020

Attachment

Dorsal D-Ring - Lanyard attached (A), Sternal Webbing (A) - use both loops together




2 / 3



MAT. 45 mm

Polyester



Not Fitted

Can be bought as an add on - 915075



1.95 KG



NO

SIZES



Number of adjustment buckles / automatic buckles



Confined Space Loops

MAT. D/E

Material of rings / buckles



Suspension Trauma Straps

Size Max. user weight

NSW Head Office

43 Frank Street
 Wetherill Park, NSW 2164
 02 9757 2277

WA Office

42 Mulgool Road
 Malaga, WA 6090
 08 9248 6674

QLD Office

7 Durbell Street
 Acacia Ridge, QLD 4110
 07 3272 0777

VIC Office

47 Technology Drive
 Sunshine West, VIC 3020
 03 9314 5525